



Talend ESB System Management Integration

User Guide

6.3.2

Adapted for v6.3.2. Supersedes previous releases.

Publication date: September 7, 2017

Copyright © 2017 Talend Inc. All rights reserved.

Copyright

This documentation is provided under the terms of the Creative Commons Public License (CCPL). For more information about what you can and cannot do with this documentation in accordance with the CCPL, please read: <http://creativecommons.org/licenses/by-nc-sa/2.0/>

This document may include documentation produced at The Apache Software Foundation which is licensed under The Apache License 2.0.

Notices

Talend and Talend ESB are trademarks of Talend, Inc.

Apache CXF, CXF, Apache Karaf, Karaf, Apache Cellar, Cellar, Apache Camel, Camel, Apache Maven, Maven, Apache Archiva, Archiva, Apache Syncope, Syncope, Apache ActiveMQ, ActiveMQ, Apache Log4j, Log4j, Apache Felix, Felix, Apache ServiceMix, ServiceMix, Apache Ant, Ant, Apache Derby, Derby, Apache Tomcat, Tomcat, Apache ZooKeeper, ZooKeeper, Apache Jackrabbit, Jackrabbit, Apache Santuario, Santuario, Apache DS, DS, Apache Avro, Avro, Apache Abdera, Abdera, Apache Chemistry, Chemistry, Apache CouchDB, CouchDB, Apache Kafka, Kafka, Apache Lucene, Lucene, Apache MINA, MINA, Apache Velocity, Velocity, Apache FOP, FOP, Apache HBase, HBase, Apache Hadoop, Hadoop, Apache Shiro, Shiro, Apache Axiom, Axiom, Apache Neethi, Neethi, Apache WSS4J, WSS4J are trademarks of The Apache Foundation. Eclipse Equinox is a trademark of the Eclipse Foundation, Inc. SoapUI is a trademark of SmartBear Software. Hyperic is a trademark of VMware, Inc. Nagios is a trademark of Nagios Enterprises, LLC.

All other brands, product names, company names, trademarks and service marks are the properties of their respective owners.

This product includes software developed at AOP Alliance (Java/J2EE AOP standards), ASM, AntLR, Apache ActiveMQ, Apache Ant, Apache Avro, Apache Axiom, Apache Axis, Apache Axis 2, Apache Batik, Apache CXF, Apache Camel, Apache Chemistry, Apache Common Http Client, Apache Common Http Core, Apache Commons, Apache Commons Bcel, Apache Commons JXPath, Apache Commons Lang, Apache Derby Database Engine and Embedded JDBC Driver, Apache Geronimo, Apache Hadoop, Apache Hive, Apache HttpClient, Apache HttpComponents Client, Apache JAMES, Apache Log4j, Apache Lucene Core, Apache Neethi, Apache POI, Apache Pig, Apache Qpid-Jms, Apache Tomcat, Apache Velocity, Apache WSS4J, Apache WebServices Common Utilities, Apache Xml-RPC, Apache Zookeeper, Box Java SDK (V2), CSV Tools, DataStax Java Driver for Apache Cassandra, Ehcache, Ezmorph, Ganymed SSH-2 for Java, Google APIs Client Library for Java, Google Gson, Groovy, Guava: Google Core Libraries for Java, H2 Embedded Database and JDBC Driver, HsqlDB, Ini4j, JClouds, JLine, JSON, JSR 305: Annotations for Software Defect Detection in Java, JUnit, Jackson Java JSON-processor, Java API for RESTful Services, Jaxb, Jaxen, Jettison, Jetty, Joda-Time, Json Simple, MetaStuff, Mondrian, OpenSAML, Paracel JDBC Driver, PostgreSQL JDBC Driver, Resty: A simple HTTP REST client for Java, Rocoto, SL4J: Simple Logging Facade for Java, SQLite JDBC Driver, Simple API for CSS, SshJ, StAX API, StAXON - JSON via StAX, Talend Camel Dependencies (Talend), The Castor Project, The Legion of the Bouncy Castle, W3C, Woden, Woodstox : High-performance XML processor, XML Pull Parser (XPP), Xalan-J, Xerces2, XmlBeans, XmlSchema Core, Xmlsec - Apache Santuario, Zip4J, atinject, dropbox-sdk-java: Java library for the Dropbox Core API, google-guice. Licensed under their respective license.

Table of Contents

Chapter 1. Introduction	1
Chapter 2. Hyperic HQ Integration	3
2.1. Introduction to Hyperic HQ	4
2.1.1. Hyperic HQ overview	4
2.1.2. System Requirements	4
2.1.3. Release directory structure	5
2.2. Deploying the Hyperic HQ plugins	5
2.2.1. Pre-requisites for deploying the plugins	5
2.2.2. How to deploy Hyperic plugins	5
2.3. Monitoring Hyperic Plugins	8
2.3.1. Monitoring ESB Services (CXF Plugin)	8
2.3.2. Monitoring ESB Routes (Camel Plugin)	8
2.3.3. Monitoring ESB Messages (ActiveMQ Plugin)	9
2.3.4. Monitoring ESB Runtime (trun Plugin)	11
Chapter 3. Nagios Integration	13
3.1. Architecture overview of Nagios and Talend ESB	14
3.2. Installing jmx4perl plugin to Nagios	15
3.2.1. Prerequisites	15
3.2.2. Downloading the jmx4perl plugin	15
3.2.3. Building the jmx4perl plugin	15
3.3. The Jolokia agent and Talend software	17
3.3.1. Manually installing the Jolokia OSGi agent to a Talend Runtime container	17
3.3.2. The Jolokia agent and ActiveMQ	17
3.4. Using Nagios configuration templates	17
3.4.1. Syntax for adding metrics for monitoring	18
3.4.2. Talend ESB Nagios configuration template files	19
3.4.3. Preparing the configuration files for running with Nagios	20
3.5. Examples: monitoring camel-jmx, cxf-jmx and ActiveMQ samples	21
3.5.1. Build and install the camel-jmx sample applications	22
3.5.2. Configure the Nagios plugin to monitor the sample applications	22
3.5.3. Monitoring with the Nagios web interface	23
3.5.4. Build and install the cxf-jmx sample applications	24
3.5.5. Config file for Rent-a-car example	25
3.5.6. Monitoring an Apache ActiveMQ broker with Nagios	26
3.6. Resources and metrics that are being monitored	28
3.6.1. CXF services metrics	28
3.6.2. Camel routes/contexts metrics	28
3.6.3. ActiveMQ queues/topics metrics	29
3.7. Metric criteria	30
3.7.1. CXF services metrics criteria	30
3.7.2. Camel routes/contexts metrics criteria	30
3.7.3. ActiveMQ queues/topics metrics criteria	31
Chapter 4. Generic JMX Integration	33
4.1. Talend ESB - JMX support	34
4.2. Using JConsole as generic JMX Application	34
4.3. Enabling JMX for Java Camel Routes and CXF Services	35
4.3.1. JMX configuration for Camel routes	35
4.3.2. JMX configuration for CXF services	35
4.4. Using alternative JMX serviceURL for the Talend Runtime container	36



Chapter 1. Introduction

This document looks at System Management Integration tools and their use within Talend ESB.

The smooth running of the computer infrastructure is a critical part of any business. This requires constant system monitoring of network resources, to be aware of what is happening and of any problems that may arise, for example, in services being unavailable, or generating faults.

In the event of emergencies, the system can be configured to notify key personnel about the problem and can help resolve it.

These System Monitoring Tools gather information either by remote calls or via local agents from the distributed system into a central monitoring repository and provide the Administrator an up-to-date view on the system health.

Talend ESB supports explicitly:

- Open Source Hyperic HQ and its commercial version vFabric Hyperic are cross platform monitoring systems designed to monitor and control server resources. [Hyperic HQ Integration](#) will describe Hyperic HQ integration support.
- Nagios is another Open Source monitoring application. [Nagios Integration](#) will describe Nagios integration support.
- Generic JMX Monitoring: Talend ESB exposes a great set of information via JMX, and by this, monitoring solutions, who provide generic monitoring capabilities for JMX, can be used with Talend ESB. JMX configuration is described in [Generic JMX Integration](#) will describe the use of JMX, using the JConsole as an example of generic monitoring application.



Chapter 2. Hyperic HQ Integration

This chapter describes the Hyperic HQ (Open Source) and vFabric Hyperic (Commercial) support in the Talend ESB. The integration is made via four Hyperic Plugins provided with the Talend ESB and which provide metric for Services, Routes, Messages (Queues & Topics) and the Talend Runtime container as well.

2.1. Introduction to Hyperic HQ

2.1.1. Hyperic HQ overview

The smooth running of the computer infrastructure is a critical part of any business. This requires constant system monitoring of network resources, to be aware of what is happening and of any problems that may arise, for example, in services being unavailable, or generating faults. In the event of emergencies, the system can be configured to notify key personnel about the problem and can help resolve it.

Hyperic is a cross platform monitoring system which is designed to monitor and control server resources. The system implements four general functions:

- **Discovery:** HQ Agents that run on the machines in your environment automatically detect, or *auto-discover*, the software resources running on the machine. When HQ discovers a software resource, it collects key facts about it, including its type, vendor, version, and location
- **Monitoring:** HQ agents track the current state of services and servers in real time, and automatic detect abnormalities
- **Alerts:** this subsystem will notify you about problems at the resources that are monitored. Alerts can be sent to administrator using e-mail, a mobile phone or pager
- **Control:** You can use HQ for remote control and administration of your software resources. Available control actions vary by resource type

You can find further information about Hyperic at the "Hyperic" site <http://www.hyperic.com/>. For more information about installing Hyperic, please see: <http://support.hyperic.com/display/DOC/QuickStart+Installation>.

2.1.2. System Requirements

Camel and CXF management demo examples can be installed, built, and run on Windows or Linux.

There is a number of software and hardware prerequisites you should be aware of, prior to starting the installation of Talend ESB products.

For a complete list of installation requirements, compatible software and software versions, see the *Talend Installation Guide*.

In addition, the following software is required for installing, building, and running the samples:

- Maven 3.0.3 or later from Apache should be installed, and the **mvn** executable should be in your `PATH`. When running **mvn**, HTTP access to the internet is required. The local Maven repository is expected to be created in its default location, i.e. the Maven configuration should not have been modified.
- The Talend Runtime container is included in the release installation in sub-directory `container`.
- VMWare Hyperic HQ 4.6.6 Server and Agent or VMWare vFabric Hyperic 4.6.6 and 5.7.1 Server and Agent must be installed. Later or other versions might work but are not certified for use with Talend ESB.

2.1.3. Release directory structure

First, you need to download and extract the Talend ESB software (see the *Talend Installation Guide* for more details). After you unpack the Talend ESB release, the plugin files are in a subdirectory `adapters`, which is structured as follows:

```
<TalendRuntimePath>/add-ons/adapters/
  hyperic_plugins/
    activemq-plugin.jar
    camel-plugin.jar
    cxf-plugin.jar
    trun-plugin.jar
```

2.2. Deploying the Hyperic HQ plugins

2.2.1. Pre-requisites for deploying the plugins

In order to provide metrics for monitoring, the Talend Runtime container or Tomcat Web application container must be configured for remote JMX access.



The Talend Runtime container of the Talend ESB installation is already configured.

For a Tomcat web application server, you must set an environment variable when starting it:

```
CATALINA_OPTS="-Dcom.sun.management.jmxremote \
-Dcom.sun.management.jmxremote.port=6969 \
-Dcom.sun.management.jmxremote.ssl=false \
-Dcom.sun.management.jmxremote.authenticate=false"
export CATALINA_OPTS
```

This can be defined in a file:

```
set CATALINA_OPTS=...
```

On Linux, this is set at the beginning of `catalina.sh`

On Windows, it is set in `catalina.bat`.



To create MBeans that collect statistics about CXF services, you first need to make an invocation on the CXF service which registers the MBeans. Without that step, Hyperic HQ will not find metrics, as MBeans does not exist.

2.2.2. How to deploy Hyperic plugins

Hyperic recommends to use the **Plugin Manager** of its Web User Interface to install new plugins in the Hyperic Server and Agent(s) version 4.6. To do so, please follow the standard VMware Hyperic documentation for the **Plugin Manager**: <https://support.hyperic.com/display/DOCS46/Plugin+Deployment+and+Management>.



In previous versions of Hyperic, only manual deploy of plugins is available. In this case, it is recommended to use the alternative approach described below.

Copy the Hyperic plugins to these folders:

- `<HypericServer>/hq-engine/hq-server/webapps/ROOT/WEB-INF/hq-plugins`
- `<HypericAgent>/bundles/agent-<version>/pdk/plugins`

The complete information about deploying Hyperic plugins is at <http://support.hyperic.com/display/EVO/Deploy+Plugin>.

Once deployed, the new plugins are added to the **Auto-Discovery** list and can now be added to the Inventory of monitored Resources. For more information, see the section below or go to Hyperic documentation: <http://support.hyperic.com>.

2.2.2.1. Add Resources to the Inventory

Tomcat and Karaf servers must be running to enable Hyperic to discover them.

1. Start the Hyperic server, if it was not running.
2. Start the Hyperic agent, if it was not running. Otherwise, restart it.

Information on how to start/stop/restart Hyperic agent and Hyperic server is in the Hyperic documentation <http://support.hyperic.com>.

3. Open your browser and log in to Hyperic server (default `http://localhost:7080/`). You will see new discovered servers in the **Auto-Discovery**.

Resource Name	Status	Changes
<input checked="" type="checkbox"/> sop-td06 - Microsoft Windows 7	modified	server set changed
<input checked="" type="checkbox"/> Apache Camel [Karaf] 2.x	new	N/A
<input checked="" type="checkbox"/> Apache Camel [Tomcat] 2.x	new	N/A
<input checked="" type="checkbox"/> Apache CXF [Tomcat] 2.x	new	N/A
<input checked="" type="checkbox"/> Apache CXF [Karaf] 2.x	new	N/A



Sometimes servers are not detected correctly. In this case you need to restart Hyperic HQ Agent. From the `<HypericAgent>/bin` directory, restart agent with the following command:

- `hq-agent.bat restart` (on Windows)
- `sh hq-agent.sh restart` (on Linux)

4. Click the **Add to Inventory** button.
5. Click the **Resources** tab.
6. Find and select **Apache Camel(CXF) [Tomcat]([Karaf]) 2.x** from the list of servers, depending on which combination you wish to monitor. For example, you may wish to monitor Camel/Tomcat and CXF/Tomcat.

Platforms (1) Servers (9) Services (212) Compatible Groups/Clusters (0) Mixed Groups (0) Applications (0)	
Server	Server Type
<input type="checkbox"/> M I A sop-td06 ActiveMQ Embedded 5.4	ActiveMQ Embedded 5.4
<input type="checkbox"/> M I A sop-td06 Apache Camel [Karaf] 2.x	Apache Camel [Karaf] 2.x
<input type="checkbox"/> M I A sop-td06 Apache Camel [Tomcat] 2.x	Apache Camel [Tomcat] 2.x
<input type="checkbox"/> M I A sop-td06 Apache CXF [Karaf] 2.x	Apache CXF [Karaf] 2.x
<input type="checkbox"/> M I A sop-td06 Apache CXF [Tomcat] 2.x	Apache CXF [Tomcat] 2.x
<input type="checkbox"/> M I A sop-td06 HQ ActiveMQ Embedded 5.3	ActiveMQ Embedded 5.3
<input type="checkbox"/> M I A sop-td06 HQ Agent 4.5.1	HQ Agent
<input type="checkbox"/> M I A sop-td06 HQ PostgreSQL 8.2	PostgreSQL 8.2
<input type="checkbox"/> M I A sop-td06 HQ Tomcat 6.0	Apache Tomcat 6.0

GROUP | DELETE | ENABLE ALL ALERTS | DISABLE ALL ALERTS

- Select a service group.

For Camel you should see the group of the routes specified by context and name.

RESOURCES	
Group Members	Avail
<input type="checkbox"/> Camel sop-td06/camel "route1"	<input checked="" type="checkbox"/>
<input type="checkbox"/> Camel sop-td06/camelTomcat "route1"	<input checked="" type="checkbox"/>
<input type="checkbox"/> Camel sop-td06/camelTomcat "route2"	<input checked="" type="checkbox"/>
Host Server	Avail
<input type="checkbox"/> sop-td06 Apache Camel [Tomcat] 2.x	<input checked="" type="checkbox"/>

For CXF you should see the group of the services specified by port and operation.

RESOURCES	
Group Members	Avail
<input type="checkbox"/> CXF "CRMServiceProvider" "getCRMInformation"	<input checked="" type="checkbox"/>
<input type="checkbox"/> CXF "ReservationServiceProvider" "getAvailableCars"	<input checked="" type="checkbox"/>
<input type="checkbox"/> CXF "ReservationServiceProvider" "getConfirmationOfReservation"	<input checked="" type="checkbox"/>
<input type="checkbox"/> CXF "ReservationServiceProvider" "submitCarReservation"	<input checked="" type="checkbox"/>
Host Server	Avail
<input type="checkbox"/> sop-td06 Apache CXF [Karaf] 2.x	<input checked="" type="checkbox"/>

Hyperic will collect the metrics for these groups, and the initial results will be displayed.



These will subsequently be updated as the examples are run.

2.3. Monitoring Hyperic Plugins

2.3.1. Monitoring ESB Services (CXF Plugin)

The Talend ESB provides a Hyperic Plugin which can be used to monitor the Talend Studio Data Services and services which are developed in Java for the Talend ESB.

Studio services by default expose metric data (performance counter) and there is nothing special to be configured for Studio based Data Services to be available for monitoring via the Talend ESB Hyperic CXF Plugin (cxf-plugin.jar).

Note that a Service (Java or Studio Data Services) must be called at least once to show up in Hyperic as CXF only exposes the performance data after the first call via JMX.

The Talend ESB 'cxf-plugin' for Hyperic provides the following Services and Metric:

Plugin Structure:

Server: [host] "Apache CXF [Karaf] 2.7"

Services

Hyperic Service Name	Example	Remark
CXF [Full qualified Service Operation name]	CXF "{http://www.talend.org/service/}DemoService" "DemoServiceOperation"	Each service in Hyperic represents a single Service Operation

Metric per Hyperic-Service (single CXF Service Operation)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y
Throughput	Number of Checked Application Faults	10	N	N
	Number of Checked Application Faults per Minute	10	Y	Y
	Number of Invocations	10	N	N
	Number of Invocations per Minute	10	Y	Y
	Number of Logical Runtime Faults	10	N	N
	Number of Logical Runtime Faults per Minute	10	Y	Y
	Number of Runtime Faults	10	N	N
	Number of Runtime Faults per Minute	10	Y	Y
	Number of UnChecked Application Faults	10	N	N
	Number of UnChecked Application Faults per Minute	10	Y	Y
Performance	Total Handling Time	5	Y	Y

2.3.2. Monitoring ESB Routes (Camel Plugin)

The Talend ESB provides a Hyperic Plugin which can be used to monitor the Talend Studio Mediation Routes and also Camel routes services which are developed in Java, Blueprint or Spring DSL.

Routes by default expose metric data and there is nothing special to be configured to make monitoring available using the 'camel-plugin.jar'.

The Talend ESB 'camel-plugin' for Hyperic provides the following Services and Metric:

Plugin Structure:

Server: [host] "Apache Camel [Karaf] 2.12"

Hyperic Name	Service	Example	Remark
Camel	[Context Name, Route Name]	Camel DirectSEADemo-ctx "Direct_A_cDirect_1"	Each individual route (Note a single RouteBuilder Model can contain multiple routes. In this case, the context name is the same, with different route names)

Metric per Hyperic-Service (single CXF Service Operation)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y
Throughput	Exchanges Completed	10	N	N
	Exchanges Completed per Minute	10	Y	Y
	Exchanges Failed	10	N	N
	Exchanges Failed per Minute	10	Y	Y
	Exchanges Total	10	N	N
	Exchanges Total per Minute	10	Y	Y
Performance	Last Processing Time	10	Y	Y
	Max Processing Time	5	Y	Y
	Mean Processing Time	5	Y	Y
	Min Processing Time	5	Y	Y
Utilization	Total Processing Time	5	Y	Y

2.3.3. Monitoring ESB Messages (ActiveMQ Plugin)

The Talend ESB provides a Hyperic Plugin which can be used to monitor an ActiveMQ Broker either running within Talend Runtime or as a standalone broker.

The ActiveMQ Broker is by default JMX enabled. There is nothing special to be configured on the Broker to use the ESB 'activemq-plugin' for Hyperic.

The Talend ESB 'activemq-plugin' for Hyperic provides the following Services and Metric.

Note that the metric is the same as in the standard Hyperic ActiveMQ plugin but the implementation is different and the supported ActiveMQ versions are different. It is mandatory to use the activemq-plugin and to replace the standard Hyperic one to monitor the ActiveMQ Broker which are shipped with Talend ESB.

Plugin Structure:

Server: [host] "ActiveMQ [Karaf] 5.7"

Hyperic Service Name	Example	Remark
ActiveMQ [Karaf] 5.7 (Server)	ActiveMQ [Karaf] 5.7	Metric about the OSGI Container itself
ActiveMQ [Karaf] 5.7 Broker	ActiveMQ [Karaf] 5.7 tesbbroker Broker	Service per ActiveMQ broker
ActiveMQ [Karaf] 5.7 Connector	ActiveMQ [Karaf] 5.7 openwire tesbbroker Connector	Metric per Connector (for example: openwire, stomp, etc.)

Hyperic Service Name	Example	Remark
ActiveMQ [Karaf] 5.7 Queue	ActiveMQ [Karaf] 5.7 IN tesbbroker Queue	Metric per Broker/Queue (for example: Queue 'IN' on Broker 'tesbbroker')
ActiveMQ [Karaf] 5.7 Topic	ActiveMQ [Karaf] 5.7 IN tesbbroker Topic	Metric per Broker/Topic (for example: Topic 'CustomerInfo' on Broker 'tesbbroker')

Metric per Hyperic-Service (ActiveMQ [Karaf] 5.x (Server))

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	5	Y	Y
	Process Start Time	5	N	N
Utilization	Child Processes	5	N	N
	Process Cpu System Time	10	N	N
	Process Cpu System Time per Minute	10	N	N
	Process Cpu Total Time	10	N	N
	Process Cpu Total Time per Minute	10	N	N
	Process Cpu Usage	10	Y	Y
	Process Cpu User Time	10	N	N
	Process Cpu User Time per Minute	10	N	N
	Process Open File Descriptors	5	N	N
	Process Page Faults	10	N	N
	Process Page Faults per Minute	10	N	N
	Process Resident Memory Size	5	Y	Y
	Process Threads	5	N	N
	Process Virtual Memory Size	5	N	N

Metric per Hyperic-Service (ActiveMQ [Karaf] 5.x Broker)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y
Utilization	Memory Limit	5	N	N
	Memory Percent Usage	5	N	N
	Total Consumer Count	5	N	N
	Total Dequeue Count	10	N	N
	Total Dequeue Count per Minute	10	N	N
	Total Enqueue Count	10	N	N
	Total Enqueue Count per Minute	10	N	N
	Total Message Count	10		
	Total Message Count per Minute	10	Y	Y

Metric per Hyperic-Service (ActiveMQ [Karaf] 5.x Connector)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y

Metric per Hyperic-Service (ActiveMQ [Karaf] 5.x Queue)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y
Utilization	Consumer Count	5	N	N
	Dequeue Count	10	N	N

Category	Name	Collection Interval (min)	Default on	Indicator
	Dequeue Count per Minute	10	Y	Y
	Enqueue Count	10	N	N
	Enqueue Count per Minute	10	Y	Y
	Memory Percent Usage	5	N	N
	Queue Size	5	Y	Y

Metric per Hyperic-Service (ActiveMQ [Karaf] 5.x Topic)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y
Utilization	Consumer Count	5	N	N
	Dequeue Count	10	N	N
	Dequeue Count per Minute	10	Y	Y
	Enqueue Count	10	N	N
	Enqueue Count per Minute	10	Y	Y
	Memory Percent Usage	5	N	N
	Queue Size	5	Y	Y

2.3.4. Monitoring ESB Runtime (trun Plugin)

The Talend ESB provides a Hyperic Plugin which can be used to monitor the Talend Runtime (OSGi Container).

The Talend Runtime container is by default JMX enabled and there is nothing special to configure to monitor the Talend Runtime container with the trun-plugin in Hyperic.

The Talend ESB 'trun-plugin' for Hyperic provides the following Services and Metric:

Plugin Structure:

Server: [host] "Talend Runtime "

Hyperic Service Name	Example	Remark
Talend Runtime		Metric about the OSGI Container itself
Talend Runtime Job Server	Talend Runtime 6.3.2 Job Server	Metric about the Job Server (for Data Integration Jobs) running within the Talend Runtime container. (The trun plugin for Hyperic does not support the standalone 'Job Server') (Subscription products only)
Talend Runtime JVM	Talend Runtime 6.3.2 JVM	Important JVM values (Subscription products only)

Metric per Hyperic-Service (Talend Runtime)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	5	Y	Y
Utilization	#Bundles - Active	5	Y	Y
	#Bundles - Installed	5	Y	Y
	#Bundles - Resolved	5	Y	Y
	#Bundles - Total	5	Y	Y
	#Feature Repositories	5	Y	Y
	#Features	5	Y	Y

Category	Name	Collection Interval (min)	Default on	Indicator
	#Services	5	Y	Y

Metric per Hyperic-Service (Talend Runtime Job Server)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y
Utilization	Running Executions	5	Y	Y

Metric per Hyperic-Service (Talend Runtime JVM)

Category	Name	Collection Interval (min)	Default on	Indicator
Availability	Availability	10	Y	Y
Utilization	Available Processors	5	Y	Y
	Heap Memory Committed	5	Y	Y
	Heap Memory Init	5	Y	Y
	Heap Memory Max	5	Y	Y
	Heap Memory Used	5	Y	Y
	NonHeap Memory Committed	5	Y	Y
	NonHeap Memory Init	5	Y	Y
	NonHeap Memory Max	5	Y	Y
	NonHeap Memory Used	5	Y	Y



Chapter 3. Nagios Integration


Nagios is an Open Source monitoring application which allows users to identify infrastructure problems before they impact on important business processes. Nagios monitors the entire IT infrastructure to ensure services, applications and business processes are working as expected.

In the case of critical problems in the infrastructure, Nagios can alert the IT department. That allows them to start fixing any issues as early as possible, before they affect the business processes.

In this chapter we describe how to monitor the Talend ESB infrastructure using Nagios.

3.1. Architecture overview of Nagios and Talend ESB

This is a diagram of how the Nagios functionality is integrated into Talend ESB - typically, the Nagios server is monitoring the OSGi container on the right, which may be a Talend Runtime container:



Jmx4Perl provides an alternative way of accessing JMX (Java Management Extensions) on JEE Servers or OSGi containers. It uses an agent-based approach where a small Java Web application (Jolokia), is deployed on the application server, and provides HTTP/JSON-based access to JMX MBeans registered within the application server.

In Talend ESB, for convenience, Jolokia has been integrated into the Talend Runtime container as an OSGi agent and also integrated into ActiveMQ using a JAR file.

This table is an overview of components in the jmx4perl distribution:

Component	Description
jmx4perl plugin	This installed on the same machine as Nagios; it communicates with a Jolokia agent which is integrated with the Talend ESB containers.
Jolokia	Jolokia is an HTTP/JSON bridge for efficient remote JMX access. It is a separate agent that resides on the monitored server, and works with the jmx4perl plugin. Jolokia is based on a set of Perl modules, and does not need a local Java installation. It is pre-installed into Talend ESB containers and ActiveMQ.
check_jmx4perl	A command utility on the Nagios server that can be used to get the monitored data - it is part of the jmx4perl distribution.
JMX::Jmx4Perl	a Perl library, for programmatic JMX access.



For more information, see:

- Nagios: <http://www.nagios.com>
- Jolokia: <http://www.jolokia.org>
- Jmx4perl: <http://labs.consol.de/jmx4perl>

3.2. Installing jmx4perl plugin to Nagios

In this section we describe how to download and install the jmx4perl plugin to a Nagios server.

3.2.1. Prerequisites

Nagios Open Source version or Nagios XI 2011 version should be installed into Linux platform (or VM). To download Nagios, go to <http://www.nagios.org/download>, and follow the installation instructions.

Note: Nagios Open Source 3.3.1 and Nagios XI 2011 version have been tested, but previous versions of Nagios may also work with Talend Runtime.

You also need an installation of the Talend Runtime, which may be on different host (for example, a Windows machine) to the Nagios installation.

3.2.2. Downloading the jmx4perl plugin

Download the jmx4perl plugin to the Nagios server machine, from <http://search.cpan.org/CPAN/authors/id/R/RO/ROLAND/jmx4perl-1.05.tar.gz> to, for example, /tmp.

3.2.3. Building the jmx4perl plugin



The main commands and scripts in this section (cpan, Build.PL, the Build perl script) need to be run with root permissions, for example, as root or using `sudo`.

We use the Perl CPAN (Comprehensive Perl Archive Network) shell here to download missing dependencies.

1. Extract the jmx4perl distribution:

```
$ cd /usr/local/src
# tar zxvf /tmp/jmx4perl-1.05.tar.gz
# ln -s -f jmx4perl-1.05 jmx4perl
```

2. Install the build module:

```
# cpan
cpan[1]> install Module::Build
cpan[1]> exit
```

3. This step installs missing dependencies for jmx4perl. There are two ways of doing this:

- A Build perl script is created later in this section; if you have a Build script that was previously created (for example, during an similar installation on another machine), then it's quicker to use it here:

```
# cd /usr/local/src/jmx4perl
# ./Build installdeps
```

- If you do not have a previously-created Build script, then explicitly install jmx4perl dependencies (and accept the default values to any questions):

```
# cpan
cpan[1]> install Config::General
cpan[2]> install Crypt::Blowfish_PP
cpan[3]> install File::SearchPath
cpan[4]> install JSON
cpan[5]> install Module::Find
cpan[6]> install Nagios::Plugin
cpan[7]> install Term::Clui
cpan[8]> install Term::ReadKey
cpan[9]> install Term::ReadLine::Perl
cpan[10]> install Term::ShellUI
cpan[11]> install Term::Size
cpan[12]> exit
```

4. Run the newly-created Build.PL script, which generates the ./Build perl script:

```
# cd /usr/local/src/jmx4perl
# perl Build.PL
```



Choose 'n' in response to "Install 'jolokia'" in the following script. Jolokia is not required directly on the Nagios server host, and only needs to be installed within the monitored containers (Talend containers have it pre-installed). Adding Jolokia would require installing additional modules and has not been tested.

When running this script give the following answers:

```
Install 'jmx4perl' ? (y/n) [y] ly
Install 'check_jmx4perl' ? (y/n) [y] ly
Install 'cacti_jmx4perl' ? (y/n) [y] ly
Install 'j4psh' ? (y/n) [y] ly
Install Term::ReadLine::Gnu ? (y/n) [n] n
Install 'jolokia' ? (y/n) [y] ln
```

* see note above

Run the ./Build script to recheck all dependencies are installed:

```
# ./Build installdeps
```

5. Run the Build command:

```
# ./Build install
```

When all these steps finished successfully, the jmx4perl plugin should be installed onto Nagios.

- Check everything has been correctly installed by communicating with a Talend Runtime container (this already has an active Jolokia agent) (please replace <jolokia_host> with the host where the Talend Runtime container is running) :

```
$ check_jmx4perl -u http://<jolokia_host>:8040/jolokia --alias
```

```
MEMORY_HEAP_USED --base MEMORY_HEAP_MAX --warning 80 --critical 90
```

If you have problems getting this running, try disabling the firewall on the Jolokia (Talend Runtime container) host.

3.3. The Jolokia agent and Talend software

Jolokia is a HTTP/JSON bridge for efficient remote JMX access, and is a separate agent which was created as part of the evolution of jmx4perl.

For more information about Jolokia, see <http://www.jolokia.org/>.

For convenience, Jolokia has been integrated into the Talend Runtime container as an OSGi agent and also integrated into ActiveMQ using a JAR file (see [Architecture overview of Nagios and Talend ESB](#)).

3.3.1. Manually installing the Jolokia OSGi agent to a Talend Runtime container

The Jolokia OSGi agent has been installed by default in the Talend Runtime container. However, this section describes how to install the Jolokia OSGi agent manually, in case it was uninstalled from the container at some point.

To install a Jolokia agent to a Talend Runtime container, execute this command at the container console:

```
feature:install tesb-jmx-http-agent
```

Then, Jolokia agent bundle will be installed to the container. Run the **list** command, and the output should look like this:

```
[ 191] [Active] [      ] [      ] [ 60] Jolokia Agent (1.0.2)
```

In addition, if you access the URL <http://localhost:8040/jolokia/version>, you will see a JSON output line about version information, which indicates the Jolokia agent is running correctly.

3.3.2. The Jolokia agent and ActiveMQ

The Jolokia agent (JAR file) has been already integrated into the ActiveMQ distribution (included in Talend ESB). It's ready to use out of the box. For an example of monitoring an ActiveMQ broker, see [Monitoring an Apache ActiveMQ broker with Nagios](#)

3.4. Using Nagios configuration templates

In this section we look at configuring Nagios to select the metrics you wish to monitor.

In [Syntax for adding metrics for monitoring](#) we look in detail at the syntax in the configuration files.

In [Talend ESB Nagios configuration template files](#) we look at the relevant configuration files that ship with Talend software.

Finally, in [Preparing the configuration files for running with Nagios](#) we use these configuration templates to configure the Nagios software, and then run the Nagios server to monitor the specified functionality.

3.4.1. Syntax for adding metrics for monitoring

You can add the metrics for monitoring using the following steps and examples (these are already defined as much as possible for the shipped examples):

1. Edit the applicable configuration file or template in the Talend Runtime.
2. Define Check definition structures for the jmx4perl plugin, corresponding to the metrics that need to be monitored.
3. Define one or more commands for Nagios, that make use of the `check_jmx4perl` command from the plugin.
4. Describe a host and service definition for Nagios; the service definition needs to use the command defined in the previous step.



`jolokia_host` is the host where the Jolokia agent is installed, and is being monitored by the `jmx4perl` plugin.

You need to substitute this with a hostname or ip address for commands, or add it to `/etc/hosts` as described in [Preparing the configuration files for running with Nagios](#) (recommended)

Here are some corresponding examples of using these steps in the shipped Talend software configuration files. In particular, we look at the structures needed to define a metric for monitoring Active MQ:

1. First we look at the configuration file `<TalendRuntimePath>/add-ons/adapters/nagios/template/activemq.cfg`
2. In particular, look at a Check definition for ActiveMQ:

```
# Define server connection parameters
<Server tesb_activemq>
  Url = http://jolokia_host:8161/jolokia
</Server>

# checks for ActiveMQ metrics
<Check Broker_TotalConsumerCount>
  MBean = org.apache.activemq:BrokerName=$0,Type=Broker
  Attribute = TotalConsumerCount
  Name = TotalConsumerCount
  Warning 1000000
</Check>
```

(See note about `jolokia_host`).

3. Here is an example of a command definition, which is in the file `<TalendRuntimePath>/add-ons/adapters/nagios/template/jmx_commands.cfg`:

```
# Define a command to monitor ActiveMQ using Nagios
# $USER5$ - user macros defining folder with check_jmx4perl
# $USER6$ - user macros defining folder with command configuration file
# $ARG1$ - check name which defined in activemq.cfg
# $ARG2$ - set broker name for activemq to be monitored
# $ARG3$ - set destination for queue to be monitored
# $ARG4$ - set destination for topic to be monitored
define command {
  command_name check_jmx4perl_activemq
```

```

command_line $USER5$/check_jmx4perl \
    --config $USER6$/activemq.cfg \
    --server $HOSTNAME$ \
    --check $ARG1$ $ARG2$ $ARG3$ $ARG4$
}

```

Note that the command definition specifies the configuration file `activemq.cfg` which contains all the check definitions defined earlier.

Several arguments are used in this command; setting their values is described in [Preparing the configuration files for running with Nagios](#).

4. In the following configuration example (in the file `<TalendRuntimePath>/add-ons/adapters/nagios/sample/activemq_host.cfg`) you can see how to describe the host and service definition for Nagios:

```

# Define a host
define host{
    use          activemq-host      ; Name of host template to use.
                                ; This host definition will inherit
                                ; all the variables that are defined
                                ; in (or inherited by) the linux-server
                                ; host template definition.

    host_name    tesb_activemq
    alias        tesb_activemq
}

define service {
    use          generic-service
    service_description Broker_TotalConsumerCount
    display_name Broker_TotalConsumerCount:
    check_interval 1
    host_name    tesb_activemq
    check_command check_jmx4perl_activemq!Broker_TotalConsumer
Count!localhost!example.A!ActiveMQ.Advisory.Consumer.Queue.example.A
}

```

Note that you need to specify the values of the `check_command` properties in a strict order:

1. the name of command used to check the metric ("check_jmx4perl_activemq" from `jmx_commands.cfg`)
2. the name of check you use, from `jmx4perl` configuration ("Broker_TotalConsumerCount" from `activemq.cfg`)
3. the arguments for the command

3.4.2. Talend ESB Nagios configuration template files

Note that Talend configuration files for Nagios are only available in the Talend Open Studio for ESB and Talend ESB download packages at the moment. They are in the `<TalendRuntimePath>/add-ons/adapters/nagios` directory.

There are four pre-defined configuration template files which ship with Talend ESB - these contain the Check definitions. These can be used for monitoring metrics of CXF, Camel and ActiveMQ resources.

File	Description
<code>jmx_commands.cfg</code>	defines three commands for Nagios monitoring, including <code>check_jmx4perl_cxf</code> , <code>check_jmx4perl_camel</code> and <code>check_jmx4perl_activemq</code> commands. Each command has several macros which need to be defined in the <code>etc/resources.cfg</code> of Nagios.
<code>cxf.cfg</code>	check definition for cxf metrics to be monitored.
<code>camel.cfg</code>	check definition for camel metrics to be monitored.

File	Description
activemq.cfg	check definition for activemq metrics to be monitored.

In addition, there are three sample `xxx_host.cfg` configuration files which provided most of the useful metrics monitoring for CXF, Camel and ActiveMQ - these contain the service and host definitions. You can define your own `xxx_host.cfg` for monitoring specific metrics and specific resources (CXF services, Camel routes, and so on):

File	Description
cxf_host.cfg	sample configuration of host and service definition for CXF monitoring.
camel_host.cfg	sample configuration of host and service definition for Camel monitoring.
activemq_host.cfg	sample configuration of host and service definition for ActiveMQ monitoring.

3.4.3. Preparing the configuration files for running with Nagios



In these examples, the Nagios installation directory may vary; typically it is in `/usr/local/nagios`, but it may not be this on all installations.

Similarly, the place to add configuration files Nagios directory is typically, but not always, `/usr/local/nagios/etc/objects`, which you may need to create if it has not been created by the installation.

You can use commands defined in `jmx_commands.cfg` file to monitor CXF services, Camel Context and Routes, ActiveMQ Broker, Topics and Queues.

In order to do it, you do not need to change template files `jmx_commands.cfg`, `cxf.cfg`, `camel.cfg`, `activemq.cfg` which already contain all check definitions and commands for these entities. For your own application, we suggest you add your own `new_host.cfg` to monitor your own cxf service, camel route, and so on, using `cxf_host.cfg`, `camel_host.cfg` and `activemq_host.cfg` as samples.

The process is as follows (see [Configure the Nagios plugin to monitor the sample applications](#) for an example of following this process with the shipped examples):

1. Define `jolokia_host` in `/etc/hosts` - this name is used in subsequent files, rather than hard-coding in the ip address.

For configuration templates `jolokia_host` means the host that has the Jolokia agent installed and would be monitored by the `jmx4perl` plugin. For example:

```
192.168.1.101 jolokia_host
```

2. Put the configuration files into the configuration folder, for example, `/usr/local/nagios/etc/objects/` or `/etc/nagios3/etc/objects/`.

The configuration files are in `<TalendRuntimePath>/add-ons/adapters/nagios`.

Copy template and sample configuration files from this directory into, for example, `/usr/local/nagios/etc/objects/` or `/etc/nagios3/etc/objects/`, for example:

```
# cp -f <TalendRuntimePath>/add-ons/adapters/nagios/template/*.cfg /usr/local/nagios/etc/objects/
```

```
# cp -f <TalendRuntimePath>/add-ons/adapters/nagios/sample/*.cfg /usr/local/nagios/etc/objects/
```

3. Add the command configuration file to the existing `nagios.cfg`, here are some examples, which depend on where your installation puts config files:

In `/usr/local/nagios/etc/nagios.cfg`, add this line:

```
cfg_file=/usr/local/nagios/etc/objects/jmx_commands.cfg
```

Or in `/etc/nagios3/nagios.cfg` add this line:

```
cfg_file=/etc/nagios3/etc/objects/jmx_commands.cfg
```

4. [Note: this step is not needed for samples, the shipped files are sufficient] Create host definitions file, for example `new_host.cfg`, by, for example, copying `jmx_host.cfg`. Note that you may need to edit it and add applications-specific service definitions.

5. [Note: this step is not needed for samples, the shipped files are sufficient]

Add the file to the existing `nagios.cfg`, here are some examples, which depend on where your installation puts config files:

In `/usr/local/nagios/etc/nagios.cfg` add this line:

```
cfg_file=/usr/local/nagios/etc/objects/new_host.cfg
```

Or in `/etc/nagios3/nagios.cfg` add this line:

```
cfg_file=/etc/nagios3/etc/objects/new_host.cfg
```

6. Define macros which will be used by `jmx_commands.cfg` in the existing `resource.cfg`; here are some examples, which depend on where your installation puts config files:

In `/usr/local/nagios/etc/resource.cfg` add these lines:

```
# set the path which jmx4perl plugin installed
$USER5$=/usr/local/src/jmx4perl/scripts
# set the path to where to find configuration files
$USER6$=/usr/local/nagios/etc/objects
```

Or in `/etc/nagios3/resource.cfg` add these lines:

```
# set the path which jmx4perl plugin installed
$USER5$=/usr/local/src/jmx4perl/scripts
# set the path to where to find configuration files
$USER6$=/etc/nagios3/etc/objects
```

7. Then, restart Nagios for the changes to take effect.

```
# service nagios restart
```

Note: the name of this service may vary, depending on which package you used to install Nagios, so it may be called, for example, `nagios3`, instead of `nagios`.

3.5. Examples: monitoring camel-jmx, cxf-jmx and ActiveMQ samples

There are two sample applications that ship with the Talend Runtime: `camel-jmx` and `cxf-jmx`, in the `<TalendRuntimePath>/examples/talend/tesb` directory.

These can be built and installed on Windows or Linux. First we look at `camel-jmx`, and monitor the metrics in Nagios. Then we look at how to do the same with `cxf-jmx`.

Then we look at an example of monitoring an Apache ActiveMQ broker, using the shipped configuration files.

3.5.1. Build and install the camel-jmx sample applications

This sample consists of two parts:

1. `service/` - This is the CXF service packaged as an OSGi bundle.
2. `war/` - This module creates a WAR archive containing the service module. This is for Servlet container use only, not used in OSGi deployment.
1. From the example parent directory (`<TalendRuntimePath>/examples/talend/tesb`), run the following command to install the example parent `pom.xml` file into the local maven repo

```
mvn install --non-recursive
```

2. From the base directory of this sample, the Maven `pom.xml` file can be used to build and run the demo

```
cd camel-jmx
```

```
mvn clean install
```

Running this command will build the demo and create a WAR archive and an OSGi bundle for deploying the service either to servlet or OSGi containers

3. Start Talend Runtime container

trun.sh (on Linux)

trun.bat (on Windows)

4. Add camel-jmx example features URL. Type this command in Talend Runtime container:

```
feature:repo-add mvn:org.talend.esb.examples/camel-jmx-feature/6.3.2/xml
```

5. To install the example feature, type this command in the Talend Runtime container:

```
feature:install camel-jmx-service
```

After deploying the samples you can see the Camel MBeans and their attributes which can be monitored using the JDK's JConsole (see [Monitoring Hyperic Plugins](#)). These attributes are also included in the metrics that we will monitor with help of Nagios.

3.5.2. Configure the Nagios plugin to monitor the sample applications

Note: in Talend Open Studio for ESB or Talend ESB installations, the configuration files are in `<TalendRuntimePath>/add-ons/adapters/nagios`.

Note that there is an overview of this process in [Preparing the configuration files for running with Nagios](#)

1. Create a local directory for the configuration files if it does not exist, for example: `/usr/local/nagios/etc/objects/` or `/etc/nagios3/etc/objects/`, depending on where your installation expects them.

- Define `jolokia_host` (the host where the examples are running) in `/etc/hosts` - this name is used in subsequent files, rather than hard-coding in the ip address. For example, add the line (depending on the IP address):

```
192.168.1.101 jolokia_host
```

- Copy the template and sample configuration files into Nagios `etc/objects` subdirectory. Not all of these are needed for this example, but we will only reference the ones we need in the configuration files. For example:

```
cp -f <TalendRuntimePath>/add-ons/adapters/nagios/template/*.cfg
    /usr/local/nagios/etc/objects/
```

```
cp -f <TalendRuntimePath>/add-ons/adapters/nagios/sample/*.cfg
    /usr/local/nagios/etc/objects/
```

This target directory may be elsewhere in your installation, for example: `/etc/nagios3/etc/objects/`.

- Add the template configuration file to the existing `nagios.cfg`, here are some examples, which depend on where your installation puts config files:

In `/usr/local/nagios/etc/nagios.cfg` add:

```
cfg_file=/usr/local/nagios/etc/objects/jmx_commands.cfg
cfg_file=/usr/local/nagios/etc/objects/camel_host.cfg
```

Or in `/etc/nagios3/nagios.cfg` add:

```
cfg_file=/etc/nagios3/etc/objects/jmx_commands.cfg
cfg_file=/etc/nagios3/etc/objects/camel_host.cfg
```

- Define macros which will be used by `jmx_commands.cfg` in `resource.cfg`, here are some examples, which depend on where your installation puts config files:

In `/usr/local/nagios/etc/resource.cfg` add these lines:

```
# set the path which jmx4perl plugin installed
$USER5$=/usr/local/src/jmx4perl/scripts
# set the path to where to find configuration files
$USER6$=/usr/local/nagios/etc/objects
```

Or in `/etc/nagios3/resource.cfg` add these lines:

```
# set the path which jmx4perl plugin installed
$USER5$=/usr/local/src/jmx4perl/scripts
# set the path to where to find configuration files
$USER6$=/etc/nagios3/etc/objects
```

- Then, restart Nagios for the changes to take effect.

```
# service nagios restart
```

Note: the name of this service may vary, depending on which package you used to install Nagios, so it may be called, for example, `nagios3`, instead of `nagios`.

3.5.3. Monitoring with the Nagios web interface

Login to the Nagios Web Interface `http://<nagios_host>/<nagios_server>/` for example: `http://localhost/nagios/`, `http://192.168.1.10/nagios3/` or `http://192.168.198.5/nagios/`, and select **services** from the left hand menu.

There, you will find the status of metrics for camel-jmx example.

Host	Service	Status	Duration	Attempt	Last Check	Status Information	
localhost	Current Load	Ok	262d 12h 3m 19s	1/4	2012-05-18 06:34:10	OK - load average: 2.55, 1.90, 1.61	
	Current Users	Ok	262d 12h 2m 41s	1/4	2012-05-18 06:34:48	USERS OK - 1 users currently logged in	
	HTTP	Ok	262d 12h 2m 4s	1/4	2012-05-18 06:30:25	HTTP OK HTTP/1.1 200 OK - 2722 bytes in 0.002 seconds	
	PING	Ok	262d 12h 1m 26s	1/4	2012-05-18 06:31:03	PING OK - Packet loss = 0%, RTA = 0.06 ms	
	Root Partition	Ok	262d 12h 0m 49s	1/4	2012-05-18 06:31:40	DISK OK - free space: / 7179 MB (77% inode=84%)	
	SSH	Ok	262d 12h 0m 11s	1/4	2012-05-18 06:32:18	SSH OK - OpenSSH_5.3 (protocol 2.0)	
	Swap Usage	Ok	262d 11h 59m 34s	1/4	2012-05-18 06:32:55	SWAP OK - 100% free (255 MB out of 255 MB)	
	Total Processes	Ok	262d 11h 58m 56s	1/4	2012-05-18 06:33:54	PROCS OK: 101 processes with STATE = RSZDT	
	tesb_camel	Context_InflightExchanges	Ok	1h 1m 40s	1/3	2012-05-18 06:34:34	OK - InflightExchanges : Value 3 in range
		Context_Uptime	Ok	1h 1m 25s	1/3	2012-05-18 06:34:49	OK - Uptime : '1 hour 8 minutes' as expected
Route_ExchangesCompleted		Ok	1h 1m 21s	1/3	2012-05-18 06:34:53	OK - ExchangesCompleted : Value 824 in range	
Route_ExchangesFailed		Ok	1h 1m 6s	1/3	2012-05-18 06:35:08	OK - ExchangesFailed : Value 0 in range	
Route_ExchangesTotal		Ok	1h 1m 6s	1/3	2012-05-18 06:35:08	OK - ExchangesTotal : Value 827 in range	
Route_LastProcessingTime		Ok	1h 1m 29s	1/3	2012-05-18 06:34:45	OK - LastProcessingTime : Value 5 in range	
Route_MaxProcessingTime		Warning	1h 1m 9s	3/3	2012-05-18 06:35:05	WARNING - MaxProcessingTime : Threshold '20' failed for value 59	

3.5.4. Build and install the cxf-jmx sample applications

This sample is in <TalendRuntimePath>/examples/talend/tesb/cxf-jmx directory and consists of a number of parts:

Directory	Description
client/	a sample client application that uses the CXF JAX-WS API to create a SOAP client and make several calls with it.
common/	code that is common for both the client and the server.
features/	example features for use in OSGi deployment.
service/	the CXF web service provider packaged as an OSGi bundle.
war/	A WAR archive containing code from common and service modules. This is for Servlet container use only, not used in OSGi deployment.

- From the base directory of the sample, the maven pom.xml file can be used to build and run the demo

```
cd cxf-jmx
```

```
mvn install
```

- Start Talend Runtime container:

```
trun.sh (on Linux)
```

```
trun.bat (on Windows)
```

- Add cxf-jmx example features URL. Type this command in Talend Runtime container:

```
feature:repo-add mvn:org.talend.esb.examples/cxf-jmx-feature/6.3.2/xml
```

- Install cxf-jmx example feature into the Talend Runtime container

```
feature:install cxf-jmx-service
```

- You can find wsdl at <http://localhost:8040/services/simpleService?wsdl>.

- Now run the client; from cxf-jmx folder run:

```
mvn exec:java -pl client
```

Note: this will include some deliberate errors (to simulate failed requests), which you can ignore:

```
[...]
Hi Alex!
Hi Alex!
Hi Alex!
2
4
6
8
10
[WARNING]
java.lang.reflect.InvocationTargetException
    at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
[...]
```

7. After the SOAP calls on the web service have completed, in JConsole, under `org.apache.cxf` you'll see the `Performance.Counter.Server` folder, where CXF MBeans with their attributes will be listed (see [Monitoring Hyperic Plugins](#) for more details).

Now we do the Nagios monitoring:

1. Add the template configuration file to the existing `nagios.cfg`, here are some examples, which depend on where your installation puts config files:

In `/usr/local/nagios/etc/nagios.cfg` add:

```
cfg_file=/usr/local/nagios/etc/objects/cxf_host.cfg
```

Or in `/etc/nagios3/nagios.cfg` add:

```
cfg_file=/etc/nagios3/etc/objects/cxf_host.cfg
```

2. Then, restart Nagios for the changes to take effect.

```
# service nagios restart
```

Note: the name of this service may vary, depending on which package you used to install Nagios, so it may be called, for example, `nagios3`, instead of `nagios`.

3. Login to the Nagios Web Interface `http://<nagios_host>/<nagios_server>/` for example: `http://localhost/nagios/`, `http://192.168.1.10/nagios3/` or `http://192.168.198.5/nagios/`.

There, you will find the status of metrics for `cxf-jmx` example.

3.5.5. Config file for Rent-a-car example

As a further example, here is the `new_host.cfg` file for the Rent-a-Car basic example (the host definitions are the same as the `cxf_host.cfg` file and have been omitted):

```
define service {
    use                generic-service
    service_description TESB_RAC_CRMSERVICE
    display_name       TESB_RAC_CRMSERVICE
    check_interval     1
    host_name          tesb_cxf
    check_command      check_jmx4perl_cxf!EndpointState!CRMSERVICEProvider!{http://services.talend.org/CRMSERVICE}CRMSERVICEProvider
}
}
```

```

define service {
    use                generic-service
    service_description TESB_RAC_ReservationService
    display_name       TESB_RAC_CRMService
    check_interval     1
    host_name          tesb_cxf
    check_command      check_jmx4perl_cxf!EndpointState!ReservationServiceProvider!{http://services.talend.org/ReservationService}ReservationServiceProvider
}

define service {
    use                generic-service
    service_description ReservationService_ANY_FAULTS
    display_name       ReservationService_ANY_FAULTS
    check_interval     1
    host_name          tesb_cxf
    check_command      check_jmx4perl_cxf!AnyFaults!ReservationServiceProvider!{http://services.talend.org/ReservationService}ReservationServiceProvider
}

```

You can run the example, add `new_host.cfg` to the `nagios.cfg` as before, restart Nagios, and view the metrics.

3.5.6. Monitoring an Apache ActiveMQ broker with Nagios



For more details on running and configuring Apache ActiveMQ, see *Talend ESB Infrastructure Services Configuration Guide*.

The process is to start an Apache ActiveMQ standalone broker on the `jolokia_host` machine, and then monitor it on the Nagios machine. The Jolokia agent (JAR file) has been already integrated into the ActiveMQ distribution which is included in Talend ESB.

1. On the `jolokia_host` machine, we start the Apache ActiveMQ standalone broker which is to be monitored; in a command console:
 - `cd <TalendRuntimePath>/activemq/bin/activemq console` (Linux*)
 - `cd <TalendRuntimePath>/activemq/bin/activemq` (Windows)


The Apache ActiveMQ broker should now be running.

*Note the "console" option in Linux runs the broker in the foreground; the default is to run it in the background.

2. You can view this using the Web Console at `http://localhost:8161/admin/`; if you access the URL `http://localhost:8161/jolokia/version`, you will see a JSON output line about version information, which indicates the Jolokia agent is running correctly.

We use this Web Console to define information to be monitored - these correspond to pre-configured entries in the check command in the Talend ESB configuration `<TalendRuntimePath>/add-ons/adapters/nagios/template/activemq_host.cfg`.

3. Create a **Queue** with the name `example.A`.
4. Create a **Topic** with the name `ActiveMQ.Advisory.Consumer.Queue.example.A`.



Topic Name

Topics

Name ↑	Number Of Consumers	Messages Enqueued	Messages Dequeued	Operations
ActiveMQ.Advisory.Consumer.Queue.example.A	0	0	0	Send To Delete
ActiveMQ.Advisory.Queue	0	1	0	Send To Delete

Now we configure the Nagios machine to do the monitoring:

1. Check that the value of `jolokia_host` in `/etc/hosts` corresponds to the machine running the Apache ActiveMQ broker, for example:

```
192.168.1.101 jolokia_host
```

2. Copy the configuration files `activemq.cfg`, `activemq_host.cfg` and `jmx_commands.cfg` from the `<TalendRuntimePath>/add-ons/adapters/nagios/template` directory to the Nagios configuration folder, for example: `/usr/local/nagios/etc/objects/` or `/etc/nagios3/etc/objects/`

See [Syntax for adding metrics for monitoring](#) for details of the check definitions, command definitions and other configuration details for ActiveMQ which are pre-defined in these files.

3. Edit `nagios.cfg` and add:

```
cfg_file=/usr/local/nagios/etc/objects/activemq_host.cfg
cfg_file=/usr/local/nagios/etc/objects/jmx_commands.cfg
```

(these paths may be different, depending on your version of Nagios).

4. Define macros which will be used by `jmx_commands.cfg` in the existing `resource.cfg`; here are some examples, which depend on where your installation puts config files:

In `/usr/local/nagios/etc/resource.cfg` add these lines:

```
# set the path which jmx4perl plugin installed
$USER5$=/usr/local/src/jmx4perl/scripts
# set the path to where to find configuration files
$USER6$=/usr/local/nagios/etc/objects
```

Or in `/etc/nagios3/resource.cfg` add these lines:

```
# set the path which jmx4perl plugin installed
$USER5$=/usr/local/src/jmx4perl/scripts
# set the path to where to find configuration files
$USER6$=/etc/nagios3/etc/objects
```

- Then, restart Nagios for the changes to take effect.

```
# service nagios restart
```

Note: the name of this service may vary, depending on which package you used to install Nagios, so it may be called, for example, `nagios3`, instead of `nagios`.

- Finally, Login to the Nagios Web Interface `http://<nagios_host>/<nagios_server>/` for example: `http://localhost/nagios/`, `http://192.168.1.10/nagios3/` or `http://192.168.198.5/nagios/`, and select **services**.

There, you will find the status of metrics for ActiveMQ.

3.6. Resources and metrics that are being monitored

Here is a complete list of the default metrics for CXF, Camel and Activemq that are being monitored in Talend ESB. More detailed definitions can be found in `<TalendRuntimePath>/add-ons/adapters/nagios/template/cxf.cfg`, `camel.cfg` and `activemq.cfg`.

3.6.1. CXF services metrics

Name	MBean	Attribute
NumInvocations	org.apache.cxf:bus.id=*,type=Performance.Counter.Server,service="\$1",port="\$0"	NumInvocations
TotalHandlingTime	org.apache.cxf:bus.id=*,type=Performance.Counter.Server,service="\$1",port="\$0"	TotalHandlingTime
NumCheckedApplicationFaults	org.apache.cxf:bus.id=*,type=Performance.Counter.Server,service="\$1",port="\$0"	NumCheckedApplicationFaults
NumLogicalRuntimeFaults	org.apache.cxf:bus.id=*,type=Performance.Counter.Server,service="\$1",port="\$0"	NumLogicalRuntimeFaults
NumRuntimeFaults	org.apache.cxf:bus.id=*,type=Performance.Counter.Server,service="\$1",port="\$0"	NumRuntimeFaults
NumUnCheckedApplicationFaults	org.apache.cxf:bus.id=*,type=Performance.Counter.Server,service="\$1",port="\$0"	NumUnCheckedApplicationFaults

3.6.2. Camel routes/contexts metrics

Name	MBean	Attribute
Context_InflightExchanges	org.apache.camel:context=*,type=context,name="\$0"	InflightExchanges
Context_Uptime	org.apache.camel:context=*,type=context,name="\$0"	Uptime
Route_ExchangesCompleted	org.apache.camel:context=*,type=routes,name="\$1"	ExchangesCompleted

Name	MBean	Attribute
Route_ExchangesFailed	org.apache.camel:context=*,type=routes,name="\$1"	ExchangesFailed
Route_ExchangesTotal	org.apache.camel:context=*,type=routes,name="\$1"	ExchangesTotal
Route_LastProcessingTime	org.apache.camel:context=*,type=routes,name="\$1"	LastProcessingTime
Route_MaxProcessingTime	org.apache.camel:context=*,type=routes,name="\$1"	MaxProcessingTime
Route_MinProcessingTime	org.apache.camel:context=*,type=routes,name="\$1"	MinProcessingTime
Route_MeanProcessingTime	org.apache.camel:context=*,type=routes,name="\$1"	MeanProcessingTime
Route_TotalProcessingTime	org.apache.camel:context=*,type=routes,name="\$1"	TotalProcessingTime

3.6.3. ActiveMQ queues/topics metrics

Name	MBean	Attribute
Broker_TotalConsumerCount	org.apache.activemq:BrokerName=\$0,Type=Broker	TotalConsumerCount
Broker_TotalDequeueCount	org.apache.activemq:BrokerName=\$0,Type=Broker	TotalDequeueCount
Broker_TotalEnqueueCount	org.apache.activemq:BrokerName=\$0,Type=Broker	TotalEnqueueCount
Broker_TotalMessageCount	org.apache.activemq:BrokerName=\$0,Type=Broker	TotalMessageCount
Broker_MemoryPercentUsage	org.apache.activemq:BrokerName=\$0,Type=Broker	MemoryPercentUsage
Broker_StorePercentUsage	org.apache.activemq:BrokerName=\$0,Type=Broker	StorePercentUsage
Broker_TempPercentUsage	org.apache.activemq:BrokerName=\$0,Type=Broker	TempPercentUsage
Queue_ConsumerCount	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	ConsumerCount
Queue_DequeueCount	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	DequeueCount
Queue_DispatchCount	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	DispatchCount
Queue_EnqueueCount	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	EnqueueCount
Queue_ExpiredCount	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	ExpiredCount
Queue_InFlightCount	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	InFlightCount
Queue_MaxEnqueueTime	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	MaxEnqueueTime
Queue_MemoryPercentUsage	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	MemoryPercentUsage
Queue_QueueSize	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	QueueSize
Queue_ProducerCount	org.apache.activemq:BrokerName=\$0,Type=Queue,Destination=\$1	ProducerCount
Topic_AverageEnqueueTime	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	AverageEnqueueTime
Topic_ConsumerCount	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	ConsumerCount
Topic_DequeueCount	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	DequeueCount
Topic_DispatchCount	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	DispatchCount
Topic_EnqueueCount	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	EnqueueCount
Topic_ExpiredCount	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	ExpiredCount

Name	MBean	Attribute
Topic_InFlightCount	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	InFlightCount
Topic_MaxEnqueueTime	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	MaxEnqueueTime
Topic_MemoryPercentUsage	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	MemoryPercentUsage
Topic_MinEnqueueTime	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	MinEnqueueTime
Topic_ProducerCount	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	ProducerCount
Topic_QueueSize	org.apache.activemq:BrokerName=\$0,Type=Topic,Destination=\$2	QueueSize

3.7. Metric criteria

This section describes the default metrics for CXF, Camel and ActiveMQ in Talend ESB, and the criteria for them signalling a state change in Nagios.

All states for Nagios checks are categorized as OK, WARNING, CRITICAL and UNKNOWN. For additional information about Nagios states see the [State types in Nagios documentation](#).

Some examples of these states are:

- All Fault metrics indicate a warning state if 1 fault has occurred and a critical state if 100 faults have occurred.
- Multicheck AnyFaults is used for fault status indication.
- All countable metrics indicate a warning state if a count of 1,000,000 reached. It can be tuned for specific needs.
- All memory usage metrics indicate a warning state when 80% of memory is used and CRITICAL if 90%.

Here is a complete metric semantics table:

3.7.1. CXF services metrics criteria

Name	State change criteria
NumInvocations	Critical 6000, Warning 5000
TotalHandlingTime	Critical 6000000, Warning 5000000
NumCheckedApplicationFaults	Critical 100, Warning 1
NumLogicalRuntimeFaults	Critical 100, Warning 1
NumRuntimeFaults	Critical 100, Warning 1
NumUnCheckedApplicationFaults	Critical 100, Warning 1

3.7.2. Camel routes/contexts metrics criteria

Name	State change criteria
Context_InflightExchanges	Critical 20, Warning 10

Name	State change criteria
Context_Uptime	Critical 6000000, Warning 5000000
Route_ExchangesCompleted	Critical 6000000, Warning 5000000
Route_ExchangesFailed	Critical 100, Warning 1
Route_ExchangesTotal	Critical 6000000, Warning 5000000
Route_LastProcessingTime	Critical 100, Warning 20
Route_MaxProcessingTime	Critical 100, Warning 20
Route_MinProcessingTime	Critical 20, Warning 10
Route_MeanProcessingTime	Critical 100, Warning 20
Route_TotalProcessingTime	Critical 6000000, Warning 5000000

3.7.3. ActiveMQ queues/topics metrics criteria

Name	State change criteria
Broker_TotalConsumerCount	Warning 1000000
Broker_TotalDequeueCount	Warning 1000000
Broker_TotalEnqueueCount	Warning 1000000
Broker_Uptime	Warning 1000000
Broker_TotalMessageCount	Warning 1000000
Broker_MemoryPercentUsage	Critical 90, Warning 80
Broker_StorePercentUsage	Critical 90, Warning 80
Broker_TempPercentUsage	Critical 90, Warning 80
Queue_ConsumerCount	Warning 1000000
Queue_DequeueCount	Warning 1000000
Queue_DispatchCount	Warning 1000000
Queue_EnqueueCount	Warning 1000000
Queue_ExpiredCount	Critical 20, Warning 10
Queue_InFlightCount	Critical 20, Warning 10
Queue_MaxEnqueueTime	Critical 400, Warning 200
Queue_MemoryPercentUsage	Critical 100, Warning 80
Queue_QueueSize	Warning 80000
Queue_ProducerCount	Warning 1000000
Topic_AverageEnqueueTime	Warning 180, Critical 400
Topic_ConsumerCount	Warning 1000000
Topic_DequeueCount	Warning 1000000
Topic_DispatchCount	Warning 1000000
Topic_EnqueueCount	Warning 1000000
Topic_ExpiredCount	Critical 40, Warning 10
Topic_InFlightCount	Warning 1000
Topic_MaxEnqueueTime	Critical 100, Warning 40
Topic_MemoryPercentUsage	Critical 90, Warning 80
Topic_MinEnqueueTime	Warning 200
Topic_ProducerCount	Warning 1000000
Topic_QueueSize	Warning 1000



Chapter 4. Generic JMX Integration

JMX facilitates the monitoring and management of Java applications. This chapter looks at:

- showing how to use the JConsole tool to view Camel route and CXF service metrics,
- overriding the standard configuration to perform more advanced ones for Camel routes and CXF services.

4.1. Talend ESB - JMX support

The Talend ESB brings support for JMX on all parts of the product. Key components of the Talend ESB expose metric information but also management operations via JMX.

4.2. Using JConsole as generic JMX Application

The JConsole which is part of the Oracle JDK, under the `/bin` folder of the JDK installation, is a generic monitoring client which allows to see JMX attributes and use JMX operations in a generic way. Here, we use the JConsole only as one example of a monitoring application which supports JMX. The information shown in the JConsole can also be used and accessed by other Monitoring solutions as long as they provide a way to use JMX.

For the JConsole, complete the following steps to see the JMX information from Talend ESB:

1. Type in **jconsole** from a commandline window. (or start the `jconsole.exe` directly from `{JAVA_HOME}/bin/jconsole.exe` in Windows, for example).
2. Set remote JMX URL by selecting **Remote Process** and click **Connect**. This opens the **Java Monitoring & Management Console**.

The default URL for Talend ESB is:

Remote Process	<code>service:jmx:rmi://localhost:44444/jndi/rmi://localhost:1099/karaf-trun</code>
Username	<code>tadmin</code>
Password	<code>tadmin</code>

3. Once connected to the service, click the tab called **MBeans**.
4. Explore the Talend ESB related **MBeans**:
 - `org.apache.camel` - contains all information about Routes which run on the Container. If no Routes are deployed, this node will not show in the list.
 - `org.apache.cxf` - shows all information about (SOAP/REST) Services running on the Container which uses Apache CXF as Web framework (for example, as the ESB Data Services do). Please be aware that this node only shows in case a service has received at least one request.
 - `org.apache.activemq` - shows all metric and management operations for the message broker (Apache ActiveMQ).
 - `org.apache.karaf` - shows the metric and management operations for the Talend Runtime container (based on Apache Karaf).
 - `TalendAgent` (commercial editions only) - shows the Operating System and Data Integration JobServer information.

There are additional **MBeans** which can be seen and used even so the above five are the most important ones for ESB.

4.3. Enabling JMX for Java Camel Routes and CXF Services

You can take the default JMX configuration which facilitates monitoring and management of Java applications but you can also override this default configuration and perform a more advanced one. For more information, see the below sections.

4.3.1. JMX configuration for Camel routes

Apache Camel has support for JMX and allows you to monitor a Camel managed object (for example, routes). By default, a JMX agent is enabled in Camel which means that the Camel runtime creates and registers MBean management objects with a MBeanServer instance in the VM. But if you would like to configure a JMX agent (for example to use a custom port in JMX URL) the best way to do it is adding a `jmxAgent` element inside the `camelContext` element in Spring configuration:

```
<camelContext id="camel" xmlns="http://camel.apache.org/schema/spring">
  <jmxAgent id="agent" mbeanObjectDomainName="your.domain.name">
    ...
  </jmxAgent>
</camelContext>
```

The default JMX configuration is used in both examples, but you can also configure it:

```
<jmxAgent id="agent" registryPort="port number" createConnector="true">
```

`createConnector` means that we should create a JMX connector (to allow remote management) for the MBeanServer. `registryPort` is the port for JMX.

You can set `hostName` and `domainName` for `DefaultManagementNamingStrategy`. As a default, `hostName` is the computer name and `domainName` is `org.apache.camel`

```
<bean id="naming"
  class="org.apache.camel.management.DefaultManagementNamingStrategy">
  <property name="hostName" value="localhost"/>
  <property name="domainName" value="org.apache.camel">
</bean>
```

To configure specific definitions for the Camel route object use the properties:

Property Name	Description
org.apache.camel	domain name
routes	Camel routes type
context	Camel context name
name	route name

You can find further information about configuring Camel JMX agent at the "Camel" site <http://camel.apache.org/camel-jmx.html>.

4.3.2. JMX configuration for CXF services

Each server type defines several service types such as EJBs, Connection Pools, JMS Queues, and so on. The plugin defines additional service types to provide management of CXF via custom MBeans. The service element defines a service type, for example:

Plugin object section:

```
<service name="CXF all services monitoring">
  <property name="OBJECT_NAME"
    value='org.apache.cxf:bus.id=*,type=Performance.Counter.Server,service=*,
    port=*,operation=*' />
  <metrics include="cxf" />
  <plugin type="autoinventory" />
</service>
```

In order to access custom MBeans, the plugin must define its JMX ObjectName to be used with various MBeanServer interface methods. Only one ObjectName is defined per service type using the property tag within the service tag.

To configure specific definitions for the CXF service object use properties:

Property Name	Description
org.apache.cxf:bus.id	id of specific CXF bus
service	service endpoint name
port	service port name
operation	service operation name

To enable JMX integration for CXF you need to declare the following bean in service Spring configuration:

```
<bean id="org.apache.cxf.management.InstrumentationManager"
  class="org.apache.cxf.management.jmx.InstrumentationManagerImpl">
  <property name="bus" ref="cxf" />
  <property name="usePlatformMBeanServer" value="true" />
  <property name="createMBeanServerConnectorFactory" value="false" />
  <property name="enabled" value="true" />
</bean>
```

To avoid any unnecessary runtime overhead, the performance counters measuring response time are disabled by default. To collect statistics for running services define the following bean:

```
<bean id="CounterRepository"
  class="org.apache.cxf.management.counters.CounterRepository">
  <property name="bus" ref="cxf" />
</bean>
```

For further information about configuring JMX in CXF you can find at [Apache CXF](#).

4.4. Using alternative JMX serviceURL for the Talend Runtime container

The Talend Runtime container allows you to change the default JMX serviceURL to an alternative one.

The default JMX serviceURL is defined in the `<TalendRuntimePath>/container/etc/org.apache.karaf.management.cfg` configuration file as shown below:

```
serviceUrl = service:jmx:rmi://${rmiServerHost}:${rmiServerPort}/jndi/rmi://
${rmiRegistryHost}:${rmiRegistryPort}/karaf-${karaf.name}
```

To use an alternative URL, just change this field as needed. For example:

```
serviceUrl = service:jmx:rmi://${rmiServerHost}:${rmiServerPort}/jndi/rmi://
${rmiRegistryHost}:${rmiRegistryPort}/jmxrmi
```


It is only recommended to do this change if the external system you want to use to communicate with Talend Runtime via JMX requires a specific form of this URL. Once this serviceURL is changed in the Talend Runtime container, you also have to change the server definition in the **Servers** page of the *Talend Administration Center* to provide the full serviceURL. For more information, see the description for the **Instance** field in the section on configuring execution servers in the *Talend Administration Center User Guide*. Note that the *Talend Administration Center* is only available in the subscription versions of the Talend ESB.

