



# Talend ESB Mediation Developer Guide

## 6.5.1

# Contents

Introduction to Apache Camel with Talend ESB.....	3
Apache Camel Enterprise Integration Patterns.....	3
Apache Camel Components.....	8
Talend ESB Mediation Examples.....	15

## Introduction to Apache Camel with Talend ESB

Talend ESB provides a fully supported, stable, production ready distribution of the industry leading open source integration framework Apache Camel. Apache Camel uses the well known Enterprise Integration Patterns and Components to make message based system integration simpler yet powerful and scalable.

The Apache Camel uses a lightweight, component based architecture which allows great flexibility in deployment scenarios, for example, stand-alone JVM applications or embedded in a servlet container such as Tomcat, or within a JEE server, or in an OSGi container such as Equinox.

Apache Camel and Talend ESB come out of the box with an impressive set of available components for all commonly used protocols like http, https, ftp, xmpp, rss and many more. A large number of data formats like EDI, JSON, CSV, HL7 and languages like JS, Python, Scala, are supported out of the box. Its extensible architecture allows developers to easily add support for proprietary protocols and data formats.

The Talend ESB distribution supplements Apache Camel with support for OSGi deployment, support for integrating Talend Routes on Camel routes and a number of advanced examples. Its OSGi container uses Apache Karaf, a lightweight container providing advanced features such as provisioning, hot deployment, logger system, dynamic configuration, complete shell environment, and other features.

## Apache Camel Enterprise Integration Patterns

This document lists the Apache Camel Enterprise Integration Patterns (EIPs) supported by Talend ESB.

This release of Talend ESB supports Apache Camel 2.17.6.

Click the links in the table to go to the Apache Camel's website for the latest information of the these EIPs.

### Enterprise Integration Patterns: Messaging Systems

Enterprise Integration Pattern	Description
Message Channel ( <a href="http://camel.apache.org/message-channel.html">http://camel.apache.org/message-channel.html</a> )	Enables one application to communicate with another using messaging.
Message ( <a href="http://camel.apache.org/message.html">http://camel.apache.org/message.html</a> )	Enables two applications connected by a message channel to exchange information.
Pipes and Filters ( <a href="http://camel.apache.org/pipes-and-filters.html">http://camel.apache.org/pipes-and-filters.html</a> )	Performs complex processing on a message while maintaining independence and flexibility.

<b>Enterprise Integration Pattern</b>	<b>Description</b>
Message Router ( <a href="http://camel.apache.org/message-router.html">http://camel.apache.org/message-router.html</a> )	Decouples individual processing steps so that messages can be passed to different filters depending on a set of conditions.
Message Translator ( <a href="http://camel.apache.org/message-translator.html">http://camel.apache.org/message-translator.html</a> )	Enables systems using different data formats to communicate with each other using messaging.
Message Endpoint ( <a href="http://camel.apache.org/message-endpoint.html">http://camel.apache.org/message-endpoint.html</a> )	Enables an application connect to a messaging channel to send and receive messages.

## Enterprise Integration Patterns: Messaging Channels

<b>Enterprise Integration Pattern</b>	<b>Description</b>
Point to Point Channel ( <a href="http://camel.apache.org/point-to-point-channel.html">http://camel.apache.org/point-to-point-channel.html</a> )	Enables the caller to be sure that exactly one receiver will receive the document or perform the call.
Publish Subscribe Channel ( <a href="http://camel.apache.org/publish-subscribe-channel.html">http://camel.apache.org/publish-subscribe-channel.html</a> )	Enables the sender to broadcast an event to all interested receivers.
Dead Letter Channel ( <a href="http://camel.apache.org/dead-letter-channel.html">http://camel.apache.org/dead-letter-channel.html</a> )	Enables the messaging system to control the behaviors if a message cannot be delivered.
Guaranteed Delivery ( <a href="http://camel.apache.org/guaranteed-delivery.html">http://camel.apache.org/guaranteed-delivery.html</a> )	Enables the sender to make sure that a message will be delivered, even if the messaging system fails.
Message Bus ( <a href="http://camel.apache.org/message-bus.html">http://camel.apache.org/message-bus.html</a> )	The architecture that enables separate applications to work together, but in a decoupled fashion such that applications can be easily added or removed without affecting the others.

## Enterprise Integration Patterns: Message Construction

<b>Enterprise Integration Pattern</b>	<b>Description</b>
Event Message ( <a href="http://camel.apache.org/event-message.html">http://camel.apache.org/event-message.html</a> )	Enables messaging to be used to transmit events from one application to another.
Request Reply ( <a href="http://camel.apache.org/request-reply.html">http://camel.apache.org/request-reply.html</a> )	Enables an applicatin to get a response from the receiver when it sends a message.
Correlation Identifier ( <a href="http://camel.apache.org/correlation-identifier.html">http://camel.apache.org/correlation-identifier.html</a> )	Enables a requestor that has received a reply to know which request the reply is for.
Return Address ( <a href="http://camel.apache.org/return-address.html">http://camel.apache.org/return-address.html</a> )	Enables a replier to know where to send the reply.

## Enterprise Integration Patterns: Message Routing

<b>Enterprise Integration Pattern</b>	<b>Description</b>
Content Based Router ( <a href="http://camel.apache.org/content-based-router.html">http://camel.apache.org/content-based-router.html</a> )	Handles the situation where the implementation of a single logical function (for example, inventory check) is spread across multiple physical systems.
Message Filter ( <a href="http://camel.apache.org/message-filter.html">http://camel.apache.org/message-filter.html</a> )	Enables a component to avoid receiving uninteresting messages.
Dynamic Router ( <a href="http://camel.apache.org/dynamic-router.html">http://camel.apache.org/dynamic-router.html</a> )	Avoids the dependency of the router on all possible destinations while maintaining its efficiency.
Recipient List ( <a href="http://camel.apache.org/recipient-list.html">http://camel.apache.org/recipient-list.html</a> )	Routes a message to a list of (static or dynamically) specified recipients.
Splitter ( <a href="http://camel.apache.org/splitter.html">http://camel.apache.org/splitter.html</a> )	Enables each of the multiple elements in a message to be processed in a different way.
Aggregator ( <a href="http://camel.apache.org/aggregator2.html">http://camel.apache.org/aggregator2.html</a> )	Combines the results of individual, but related messages so that they can be processed as a whole.
Resequencer ( <a href="http://camel.apache.org/resequencer.html">http://camel.apache.org/resequencer.html</a> )	Gets a stream of related but out-of-sequence messages back into the correct order.
Composed Message Processor ( <a href="http://camel.apache.org/composed-message-processor.html">http://camel.apache.org/composed-message-processor.html</a> )	Maintains the overall message flow when processing a message consisting of multiple elements, each of which may require different processing.

<b>Enterprise Integration Pattern</b>	<b>Description</b>
Scatter-Gather ( <a href="http://camel.apache.org/scatter-gather.html">http://camel.apache.org/scatter-gather.html</a> )	Maintains the overall message flow when a message needs to be sent to multiple recipients, each of which may send a reply.
Routing Slip ( <a href="http://camel.apache.org/routing-slip.html">http://camel.apache.org/routing-slip.html</a> )	Routes a message consecutively through a series of processing steps when the sequence of steps is not known at design-time and may vary for each message.
Throttler ( <a href="http://camel.apache.org/throttler.html">http://camel.apache.org/throttler.html</a> )	Throttles messages to ensure that a specific endpoint does not get overloaded, or an agreed SLA with some external service is not exceeded.
Sampling ( <a href="http://camel.apache.org/sampling.html">http://camel.apache.org/sampling.html</a> )	Samples one message out of many in a given period to avoid downstream route from getting overloaded.
Delayer ( <a href="http://camel.apache.org/delayer.html">http://camel.apache.org/delayer.html</a> )	Delays the sending of a message.
Load Balancer ( <a href="http://camel.apache.org/load-balancer.html">http://camel.apache.org/load-balancer.html</a> )	Balance the processing load across a number of endpoints.
Multicast ( <a href="http://camel.apache.org/multicast.html">http://camel.apache.org/multicast.html</a> )	Routes a message to a number of endpoints at the same time.
Loop ( <a href="http://camel.apache.org/loop.html">http://camel.apache.org/loop.html</a> )	Repeats processing a message in a loop.

## Enterprise Integration Patterns: Message Transformation

<b>Enterprise Integration Pattern</b>	<b>Description</b>
Content Enricher ( <a href="http://camel.apache.org/content-enricher.html">http://camel.apache.org/content-enricher.html</a> )	Communicates with another system if the message originator does not have all the required data items available.
Content Filter ( <a href="http://camel.apache.org/content-filter.html">http://camel.apache.org/content-filter.html</a> )	Simplifies dealing with a large message, when you are interested only in a few data items.
Claim Check ( <a href="http://camel.apache.org/claim-check.html">http://camel.apache.org/claim-check.html</a> )	Reduces the data volume of message sent across the system without sacrificing information content.
Normalizer ( <a href="http://camel.apache.org/normalizer.html">http://camel.apache.org/normalizer.html</a> )	Processes messages that are semantically equivalent, but arrive in a different format.

Enterprise Integration Pattern	Description
Sort ( <a href="http://camel.apache.org/sort.html">http://camel.apache.org/sort.html</a> )	Sorts the body of a message.
Validate ( <a href="http://camel.apache.org/validate.html">http://camel.apache.org/validate.html</a> )	Validates a message.

## Enterprise Integration Patterns: Messaging Endpoints

Enterprise Integration Pattern	Description
Messaging Mapper ( <a href="http://camel.apache.org/messaging-mapper.html">http://camel.apache.org/messaging-mapper.html</a> )	Moves data between domain objects and the messaging infrastructure while keeping the two independent of each other.
Event Driven Consumer ( <a href="http://camel.apache.org/event-driven-consumer.html">http://camel.apache.org/event-driven-consumer.html</a> )	Enables an application to consume messages automatically as they become available.
Polling Consumer ( <a href="http://camel.apache.org/polling-consumer.html">http://camel.apache.org/polling-consumer.html</a> )	Enables an application to consume a message when the application is ready.
Competing Consumers ( <a href="http://camel.apache.org/competing-consumers.html">http://camel.apache.org/competing-consumers.html</a> )	Enables a messaging client to process multiple messages concurrently.
Message Dispatcher ( <a href="http://camel.apache.org/message-dispatcher.html">http://camel.apache.org/message-dispatcher.html</a> )	Enables multiple consumers on a single channel to coordinate their message processing.
Selective Consumer ( <a href="http://camel.apache.org/selective-consumer.html">http://camel.apache.org/selective-consumer.html</a> )	Enables a message consumer to select which messages it wishes to receive.
Durable Subscriber ( <a href="http://camel.apache.org/durable-subscriber.html">http://camel.apache.org/durable-subscriber.html</a> )	Enables a subscriber to avoid missing messages while it's not listening for them.
Idempotent Consumer ( <a href="http://camel.apache.org/idempotent-consumer.html">http://camel.apache.org/idempotent-consumer.html</a> )	Enables a message receiver to deal with duplicate messages.
Transactional Client ( <a href="http://camel.apache.org/transactional-client.html">http://camel.apache.org/transactional-client.html</a> )	Enables a client to control its transactions with the messaging system.

Enterprise Integration Pattern	Description
Messaging Gateway ( <a href="http://camel.apache.org/messaging-gateway.html">http://camel.apache.org/messaging-gateway.html</a> )	Encapsulates access to the messaging system from the rest of the application.
Service Activator ( <a href="http://camel.apache.org/service-activator.html">http://camel.apache.org/service-activator.html</a> )	Enables an application to design a service that can be invoked both via various messaging technologies and via non-messaging techniques.

## Enterprise Integration Patterns: System Management

Enterprise Integration Pattern	Description
ControlBus ( <a href="http://camel.apache.org/controlbus.html">http://camel.apache.org/controlbus.html</a> )	Effectively administer a messaging system that is distributed across multiple platforms and a wide geographic area.
Detour ( <a href="http://camel.apache.org/detour.html">http://camel.apache.org/detour.html</a> )	Routes a message through intermediate steps to perform validation, testing or debugging functions.
Wire Tap ( <a href="http://camel.apache.org/wire-tap.html">http://camel.apache.org/wire-tap.html</a> )	Inspects messages that travel on a point-to-point channel.
Message History ( <a href="http://camel.apache.org/message-history.html">http://camel.apache.org/message-history.html</a> )	Enables analyzing and debugging the flow of messages in a loosely coupled system.
Log ( <a href="http://camel.apache.org/logaip.html">http://camel.apache.org/logaip.html</a> )	Logs the processing a message.

## Apache Camel Components

This document lists the Camel components supported by Talend ESB.

This release of Talend ESB supports Apache Camel 2.17.6.

Click the links in the table to go to the Apache Camel's website for the latest information of the these components.

Component / ArtifactId / URI	Description
<a href="#">AHC</a> (camel-ahc) ahc:httpUri	To call external HTTP services using Async Http Client.
<a href="#">AHC Websocket</a> (camel-ahc-ws) ahc-ws:httpUri	To exchange data with external Websocket servers using Async Http Client.



Component / ArtifactId / URI	Description
<a href="#">APNS</a> (camel-apns) apns:name	For sending notifications to Apple iOS devices.
<a href="#">Avro</a> (camel-avro) avro:transport:host:port/messageName	Working with Apache Avro for data serialization.
<a href="#">Atom</a> (camel-atom) atom:feedUri	For consuming Atom RSS feeds.
<a href="#">Atmosphere Websocket</a> (camel-atmosphere-websocket) atmosphere-websocket:servicePath	To exchange data with external Websocket clients using Atmosphere.
<a href="#">Braintree</a> (camel-braintree) braintree:apiName/methodName	For integrating with the Braintree Payment System.
<a href="#">Camel Context</a> (camel-context) context:contextId:localEndpointUrl	To send/receive messages between Camel routes in a black box way. This component is deprecated.
<a href="#">CMIS</a> (camel-cmis) cmis:cmsUrl	The cmis component uses the Apache Chemistry client API and allows you to add/read nodes to/from a CMIS compliant content repositories.
<a href="#">CoAP</a> (camel-coap) coap:uri	For sending and receiving messages from COAP capable devices.
<a href="#">CouchDB</a> (camel-couchdb) couchdb:protocol:hostname:port/database	To integrate with CouchDB databases.
<a href="#">Crypto (JCE)</a> (camel-crypto) crypto:cryptoOperation:name	For signing and verifying exchanges using the Signature Service of the Java Cryptographic Extension (JCE).
<a href="#">CXF</a> (camel-cxf) cxf:beanId:address	Works for SOAP WebServices using Apache CXF.
<a href="#">Disruptor</a> (camel-disruptor) disruptor:name	To provide asynchronous SEDA behavior using LMAX Disruptor.
<a href="#">EHCACHE</a> (camel-cache) cache:cacheName	To perform caching operations using EHCACHE as the Cache Implementation. This component is deprecated.

Component / ArtifactId / URI	Description
<a href="#">Elasticsearch</a> (camel-elasticsearch) elasticsearch:clusterName	For interfacing with ElasticSearch server.
<a href="#">EISQL</a> (camel-elsql) elsql:elsqlName:resourceUri	The EISQL component is an extension to the existing SQL Component that uses EISql to define the SQL queries.
<a href="#">etcd</a> (camel-etcd) etcd:namespace/path	To work with Etcd, a distributed reliable key-value store.
<a href="#">Exec</a> (camel-exec) exec:executable	To execute OS system commands.
<a href="#">Facebook</a> (camel-facebook) facebook:methodName	To provide access to all of the Facebook APIs accessible using Facebook4J.
<a href="#">Flatpack</a> (camel-flatpack) flatpack:type:resourceUri	The flatpack component supports fixed width and delimited file parsing via the FlatPack library.
<a href="#">FOP</a> (camel-fop) fop:outputType	To render a message into different output formats using Apache FOP.
<a href="#">Freemarker</a> (camel-freemarker) freemarker:resourceUri	Transforms the message using a FreeMarker template.
<a href="#">FTP</a> (camel-ftp) ftp:host:port/directoryName	For uploading or downloading files from FTP servers.
<a href="#">Geocoder</a> (camel-geocoder) geocoder:address:latlng	For looking up geocodes (latitude and longitude) for a given address or reverse lookup.
<a href="#">Git</a> (camel-git) git:localPath	For working with git repositories.
<a href="#">Guava EventBus</a> (camel-guava-eventbus) guava-eventbus:eventBusRef	Provides integration bridge between Camel and Google Guava EventBus.
<a href="#">Grape</a> (camel-grape) grape:defaultCoordinates	To fetch, load and manage additional jars when CamelContext is running.
<a href="#">HBase</a> (camel-hbase) hbase:tableName	For reading/writing from/to an HBase store (Hadoop database).

Component / ArtifactId / URI	Description
<b>HDFS</b> (camel-hdfs) hdfs:hostName:port/path	For reading/writing from/to an HDFS file system using Hadoop 1.x. This component is deprecated.
<b>HDFS2</b> (camel-hdfs2) hdfs2:hostName:port/path	For reading/writing from/to an HDFS file system using Hadoop 2.x.
<b>HTTP4</b> (camel-http4) http4:httpUri	For calling out to external HTTP servers using Apache HTTP Client 4.x.
<b>Ignite Cache</b> (camel-ignite) ignite-cache:cacheName	The Ignite Cache endpoint is one of camel-ignite endpoints which allows you to interact with an Ignite Cache.
<b>Infinispan</b> (camel-infinispan) infinispan:cacheName	For reading/writing from/to Infinispan distributed key/value store and data grid.
<b>IronMQ</b> (camel-ironmq) ironmq:queueName	The ironmq provides integration with IronMQ an elastic and durable hosted message queue as a service.
<b>JBPM</b> (camel-jbpm) jbpm:connectionURL	Provides integration with jBPM (Business Process Management).
<b>JCache</b> (camel-jcache) jcache:cacheName	To perform caching operations using JSR107/JCache as cache implementation.
<b>JCR</b> (camel-jcr) jcr:host/base	To add/read nodes to/from a JCR compliant content repository.
<b>JDBC</b> (camel-jdbc) jdbc:dataSourceName	To access databases through JDBC where SQL queries are sent in the message body.
<b>Jetty 9</b> (camel-jetty9) jetty:httpUri	Provides HTTP-based endpoints for consuming and producing HTTP requests.
<b>JGroups</b> (camel-jgroups) jgroups:clusterName	Provides exchange of messages between Camel and JGroups clusters.
<b>JMS</b> (camel-jms) jms:destinationType:destinationName	Allows messages to be sent to, or consumed from a JMS Queue or Topic.
<b>JMX</b> (camel-jmx) jmx:serverURL	To receive JMX notifications.

Component / ArtifactId / URI	Description
<b>JOLT</b> (camel-jolt) jolt:resourceUri	To process JSON messages using an JOLT specification (such as JSON-JSON transformation).
<b>JPA</b> (camel-jpa) jpa:entityType	To store and retrieve Java objects from databases using JPA.
<b>Jsch</b> (camel-jsch) scp:host:port/directoryName	To copy files using the secure copy protocol (SCP).
<b>Kafka</b> (camel-kafka) kafka:topic	Allows messages to be sent to, or consumed from Apache Kafka brokers.
<b>Krati</b> (camel-krati) krati:path	Allows the use of krati datastores and datasets inside Camel.
<b>Kubernetes</b> (camel-kubernetes) kubernetes:masterUrl	To work with Kubernetes PaaS.
<b>Lucene</b> (camel-lucene) lucene:host:operation	To insert or query from Apache Lucene databases.
<b>Mail</b> (camel-mail) imap:host:port	To send or receive emails using imap/pop3 or smtp protocols.
<b>Mina2</b> (camel-mina2) mina2:protocol:host:port	Socket level networking using TCP or UDP with the Apache Mina 2.x library.
<b>MLLP</b> (camel-mllp) mllp:hostname:port	Provides functionality required by Healthcare providers to communicate with other systems using the MLLP protocol.
<b>Mock</b> (camel-core) mock:name	For testing routes and mediation rules using mocks.
<b>MongoDB</b> (camel-mongodb) mongodb:connectionBean	For working with documents stored in MongoDB database.
<b>MongoDB GridFS</b> (camel-mongodb-gridfs) mongodb-gridfs:connectionBean	For working with MongoDB GridFS.
<b>MQTT</b> (camel-mqtt) mqtt:name	For communicating with MQTT M2M message brokers using FuseSource MQTT Client.

Component / ArtifactId / URI	Description
<b>Mustache</b> (camel-mustache) mustache:resourceUri	Transforms the message using a Mustache template.
<b>MyBatis</b> (camel-mybatis) mybatis:statement	Performs a query, poll, insert, update or delete in a relational database using MyBatis.
<b>Nats</b> (camel-nats) nats:servers	Produces and consumes messages from NATS.
<b>Netty</b> (camel-netty) netty:protocol:host:port	Socket level networking using TCP or UDP with the Netty 3.x library. This component is deprecated.
<b>OpenShift</b> (camel-openshift) openshift:clientId	To Manage your Openshift 2.x applications. This component is deprecated.
<b>OptaPlanner</b> (camel-optaplanner) optaplanner:configFile	Solves the planning problem contained in a message with OptaPlanner.
<b>Paho</b> (camel-paho) paho:topic	For communicating with MQTT M2M message brokers using Eclipse Paho MQTT Client.
<b>PDF</b> (camel-pdf) pdf:operation	Provides the ability to create, modify or extract content from PDF documents.
<b>Quartz</b> (camel-quartz) quartz:groupName/timerName	Provides a scheduled delivery of messages using the Quartz 1.x scheduler. This component is deprecated.
<b>Quartz2</b> (camel-quartz2) quartz2:groupName/triggerName	Provides a scheduled delivery of messages using the Quartz 2.x scheduler.
<b>RabbitMQ</b> (camel-rabbitmq) rabbitmq:hostname:portNumber/ exchangeName	To produce and consume messages from RabbitMQ instances.
<b>RMI</b> (camel-rmi) rmi:hostname:port/name	For invoking Java RMI beans from Camel.
<b>RSS</b> (camel-rss) rss:feedUri	For consuming RSS feeds.
<b>Salesforce</b> (camel-salesforce) salesforce:operationName:topicName	For integrating Camel with the massive Salesforce API.

Component / ArtifactId / URI	Description
<a href="#">SAP NetWeaver</a> (camel-sap-netweaver) sap-netweaver:url	To integrate with the SAP NetWeaver Gateway using HTTP transports.
<a href="#">Servlet</a> (camel-servlet) servlet:contextPath	To use a HTTP Servlet as entry for Camel routes when running in a servlet container.
<a href="#">Simple JMS</a> (camel-sjms) sjms:destinationType:destinationName	Allows messages to be sent to, or consumed from a JMS Queue or Topic (uses JMS 1.x API).
<a href="#">Slack</a> (camel-slack) slack:channel	To send messages to Slack.
<a href="#">SMPP</a> (camel-smpp) smpp:host:port	To send and receive SMS using a SMSC (Short Message Service Center).
<a href="#">SNMP</a> (camel-snmp) snmp:host:port	To poll SNMP capable devices or receiving traps.
<a href="#">Solr</a> (camel-solr) solr:url	To interface with an Apache Lucene Solr server.
<a href="#">Splunk</a> (camel-splunk) splunk:name	To publish or search for events in Splunk.
<a href="#">Spring Batch</a> (camel-spring-batch) spring-batch:jobName	To send messages to Spring Batch for further processing.
<a href="#">Spring Integration</a> (camel-spring-integration) spring-integration:defaultChannel	Bridges Camel with Spring Integration.
<a href="#">Spring LDAP</a> (camel-spring-ldap) spring-ldap:templateName	To perform searches in LDAP servers using filters as the message payload.
<a href="#">Spring Redis</a> (camel-spring-redis) spring-redis:host:port	To send and receive messages from Redis.
<a href="#">Spring WebService</a> (camel-spring-ws) spring-ws:type:lookupKey:webServiceEndpointUri	Works for SOAP WebServices using Spring WebServices.
<a href="#">SQL</a> (camel-sql) sql:query	To work with databases using JDBC SQL queries.

Component / ArtifactId / URI	Description
<b>SSH</b> (camel-ssh) ssh:host:port	The ssh component enables access to SSH servers so that you can send an SSH command and process the response.
<b>StAX</b> (camel-stax) stax:contentHandlerClass	Allows messages to be process through a SAX ContentHandler.
<b>Stomp</b> (camel-stomp) stomp:destination	For communicating with Stomp compliant message brokers.
<b>Twitter</b> (camel-twitter) twitter:kind	Integrates with Twitter to send tweets or search for tweets and more.
<b>Undertow</b> (camel-undertow) undertow:httpURI	Provides HTTP-based endpoints for consuming and producing HTTP requests.
<b>Velocity</b> (camel-velocity) velocity:resourceUri	Transforms the message using a Velocity template.
<b>Vertx</b> (camel-vertx) vertx:address	For sending and receive messages from a vertx event bus.
<b>Weather</b> (camel-weather) weather:name	Polls the weather information from Open Weather Map.
<b>Yammer</b> (camel-yammer) yammer:function	To interact with the Yammer enterprise social network.
<b>ZooKeeper</b> (camel-zookeeper) zookeeper:serverUrls/path	Allows interaction with a ZooKeeper cluster.

## Talend ESB Mediation Examples

This document lists the mediation examples provided by Talend ESB.

The samples folder of the Talend ESB download contains examples that are provided by the Apache Camel project, as well as Talend ESB-specific examples showing multiple usages of Camel routing. Each Talend ESB sample has its own README file providing a full description of the sample along with deployment information using embedded Jetty or Talend Runtime Container. The examples provided by the Apache Camel project and bundled with the Talend ESB are listed and explained on the Camel website (<http://camel.apache.org/examples.html>). The following table provides a summary of additional mediation examples provided in the Talend ESB distribution.

Example	Description
blueprint	Provides an example of deploying Camel routes as an OSGi bundle in the container.
claimcheck	EAI patterns example demonstrating use of the Claim Check, Splitter, Reswquencer and Delayer patterns.
jaxrs-jms-http	Shows how a JAX-RS service can be offered and used with Camel transports.
jaxws-jms	Shows how to publish and call a CXF service using SOAP/JMS using Camel as a CXF transport.
spring-security	Example shows how to leverage Spring Security to secure Camel routes in general and also specifically when combined with CXF JAX-WS and JAX-RS endpoints.